Standard Grade Toggle Switches

Single-Pole, 3-Way, 4-Way 15A, 120V/AC

FEATURES

- Industrial design cam action mechanism ensures quiet switch action.
- 3-way switches feature additional push-in common termination for feed-through tapping.
- Unbreakable top and bottom housing eliminates call-backs due to job site breakage.
- Push-in terminals accept #14 AWG solid wire only; side wire terminals accept up to #10 AWG solid wire.

Toggle Switches, Non-Grounding

15A 120V/AC; Side Wire & Push Wire

Description	Color Suffix	Catalog No.	4
Single-Pole	В, V, <mark>W</mark>	□ <mark>1301</mark>	•
3-Way	B, V, W	□ 1303	٠

cULus Listed to UL20, file no. E18704; NOM certified

	installations.
•	Patented built-in wire stripper for #12 and #14 AWG wire to
	speed installation.

Long, broad mounting strap virtually eliminates floating

- Patented built-in wire looper for pre-looping.
- Tri-combo screws accept Slotted, Phillips, and Robertson-head tools for installation flexibility.
- Lighted models' toggle glows in "off " position.



Toggle Switches, Grounding

15A 120V/AC; Side Wire & Push Wire

Description	Color Suffix	Catalog No.	٢
Single-Pole	A, B, LA, V, W	□ 1301-7	•
3-Way	A, B, LA, V, W	□ 1303-7	٠
4-Way	A, B, LA, V, W	□ 1242-7	٠
Single-Pole, Less Ears	A, B, LA, V, W	□ 1301-73	٠
Lighted, Single-Pole	A, LA, V, W	□ 1301-7LT	٠
Lighted, 3-Way	A, LA, V, W	□ 1303-7LT	٠

c(h) us kind cULus Listed to UL20, file no. E18704; NOM certified. Lighted models also CSA certified to C22.2, no. 111.



1301-7

1301-73

Color Ordering Information: For ordering devices, include Cat. No. followed by the color code: A (Almond), B (Brown), LA (Light Almond), V (Ivory), W (White)

Dimensional Information: B-60

Specification Information: Please visit www.cooperwiringdevices.com

NAFTA Compliant: See page F-21

